

volzMasking 3048U

volzMasking 3048U is a general purpose masking tape. It is suitable for wall paints and various industrial painting applications.

Nominal Values

Backing	Saturated Crepe Paper
Backing Thickness	0,090 mm
Adhesive Type	Natural rubber and Hydrocarbon Resins
Total Thickness	0,125 mm
Color	Ivory (00), other colors upon request
Adhesion to Steel	6,25 N/25 mm
Tensile Strength	125,00 N/25 mm
Elongation at Break	10%
Temperature Resistance	+60°C (1 h)
Length	50 m, other lengths upon request
Width	19 mm, 25 mm, 30 mm, 38 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	24 March 2025

volzMasking 3048U

Applications

- Wall painting
- Industrial painting applications

Benefits

- Good adhesion to all surfaces
- Easy removal without adhesive residue
- Heat resistant up to 60°C (1 hour)
- Easy application on curved profiles and irregular surfaces
- Compatible with solvent-based and water-based paints

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 25.05.2026