

volzMount 9050C-PV2



volzMount 9050-PV2 is a double-sided foam adhesive tape for high demands, coated with an acrylate adhesive, Covered with a white paper liner. volzMount 9050-PV2 features good initial and excellent final tack.

Nominal Values

Backing	PE Foam
Adhesive Type	Solvent Acrylic
Total Thickness	1,000 mm
Color	White (08)
Liner	White, siliconized Paper
Adhesion to Steel	25,00 N/25 mm
Tensile Strength	25,00 N/25 mm, (Schaumspaltung)
Shear Strength	> 167 h
Temperature Resistance	-40°C to +90°C
Length	66 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1250 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	02 March 2026

volzMount 9050C-PV2



Applications

- Bonding of mouldings, profiles, mirrors and glazing bars indoors and outdoors

Benefits

- Good initial and excellent final tack

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 18.06.2026