

Technical Product Data Sheet

volzMount 9050C-PV2



volzMount 9050-PV2 is a double-sided foam adhesive tape for high demands, coated with an acrylate adhesive, Covered with a white paper liner. volzMount 9050-PV2 features good initial and excellent final tack.

Nominal Values

Backing PE Foam

Adhesive Type Solvent Acrylic

Total Thickness 1,000 mm

> Color White (08)

Liner White, siliconized Paper

Adhesion to Steel 25,00 N/25 mm

Tensile Strength 25,00 N/25 mm, (Schaumspaltung)

Shear Strength > 10000 min

-40°C to +90°C **Temperature Resistance**

> Length 66 m, other lengths upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1250 Width


mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 06 December 2021







DE-79227 Schallstadt



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of











Technical Product Data Sheet

volzMount 9050C-PV2



Applications

• Bonding of mouldings, profiles, mirrors and glazing bars indoors and outdoors

Benefits


• Good initial and excellent final tack

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 03.11.2025





DE-79227 Schallstadt







