

volzMount 9050C-PV2



volzMount 9050-PV2 is a double-sided foam adhesive tape for high demands, coated with an acrylate adhesive, covered with a white paper liner. volzMount 9050-PV2 features good initial and excellent final tack.

Nominal Values

Manufacturer	VOLZ®
Backing	PE Foam
Adhesive Type	Solvent Acrylic
Total Thickness	1,000 mm
Color	White (08)
Liner	White, siliconized Paper
Adhesion to Steel	25,00 N/25 mm
Tensile Strength	25,00 N/25 mm, (Schaumspaltung)
Shear Strength	> 10000 min
Temperature Resistance	-40°C to +90°C
Length	66 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1250 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	06 December 2021

volzMount 9050C-PV2



Applications

- Bonding of mouldings, profiles, mirrors and glazing bars indoors and outdoors

Benefits

- Good initial and excellent final tack

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 16.07.2024