

# volzMount 9050C-PV2



volzMount 9050-PV2 is a double-sided foam adhesive tape for high demands, coated with an acrylate adhesive, Covered with a white paper liner. volzMount 9050-PV2 features good initial and excellent final tack.

## Nominal Values

<b>Backing</b>	PE Foam
<b>Adhesive Type</b>	Solvent Acrylic
<b>Total Thickness</b>	1,000 mm
<b>Color</b>	White (08)
<b>Liner</b>	White, siliconized Paper
<b>Adhesion to Steel</b>	25,00 N/25 mm
<b>Tensile Strength</b>	25,00 N/25 mm, ( Schaumspaltung)
<b>Shear Strength</b>	> 10000 min
<b>Temperature Resistance</b>	-40°C to +90°C
<b>Length</b>	66 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1250 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	06 December 2021

# volzMount 9050C-PV2



## Applications

- Bonding of mouldings, profiles, mirrors and glazing bars indoors and outdoors

## Benefits

- Good initial and excellent final tack

## Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 09.01.2026