

volzMount 9050L



volzMount 9050L is a double-sided, foam adhesive tape for mounting and permanent fixing to virtually all smooth and slightly uneven adhesive surfaces.

Nominal Values

Manufacturer	VOLZ®
Backing	PE Foam
Backing Thickness	1,000 mm
Adhesive Type	Acrylic, (Pure)
Total Thickness	1,150 mm
Color	White (08)
Liner	PE Paper
Shear Strength	40 N / 625mm ² , bei 23°C (± 2°C), DIN EN 1943
Temperature Resistance	-40°C to +95°C
Length	5 m, 50 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1260 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	06 December 2021

volzMount 9050L



Applications

- Assembly of mirrors in the manufacture of bedroom, living room, sanitary and wardrobe furniture
- Assembly of PVC window bars
- Assembly of small appliances and hooks on tiles and smooth walls
- Assembly of cable ducts

Benefits

- Extreme resistance to ageing, UV, weathering and plasticisers.
- The backing foam does not yellow and remains permanently elastic
- High initial adhesive strength provides sufficient application safety immediately after assembly
- Vibration-damping and compensating for different expansion coefficients of the joining partners

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 16.07.2024