

## volzMount 9050L



volzMount 9050L is a double-sided, foam adhesive tape for mounting and permanent fixing to virtually all smooth and slightly uneven adhesive surfaces.

### Nominal Values

<b>Backing</b>	PE Foam
<b>Backing Thickness</b>	1,000 mm
<b>Adhesive Type</b>	Acrylic, (Pure)
<b>Total Thickness</b>	1,150 mm
<b>Color</b>	White (08)
<b>Liner</b>	PE Paper
<b>Shear Strength</b>	40 N / 625mm <sup>2</sup> , bei 23°C (± 2°C), DIN EN 1943
<b>Temperature Resistance</b>	-40°C to +95°C
<b>Length</b>	5 m, 50 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1260 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	06 December 2021

## volzMount 9050L



### Applications

- Assembly of mirrors in the manufacture of bedroom, living room, sanitary and wardrobe furniture
- Assembly of PVC window bars
- Assembly of small appliances and hooks on tiles and smooth walls
- Assembly of cable ducts

### Benefits

- Extreme resistance to ageing, UV, weathering and plasticisers.
- The backing foam does not yellow and remains permanently elastic
- High initial adhesive strength provides sufficient application safety immediately after assembly
- Vibration-damping and compensating for different expansion coefficients of the joining partners

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 29.08.2025