

volzMount 9050L



volzMount 9050L is a double-sided, foam adhesive tape for mounting and permanent fixing to virtually all smooth and slightly uneven adhesive surfaces.

Nominal Values

Backing	PE Foam
Backing Thickness	1,000 mm
Adhesive Type	Acrylic, (Pure)
Total Thickness	1,150 mm
Color	White (08)
Liner	PE Paper
Shear Strength	40 N / 625mm ² , bei 23°C (± 2°C), DIN EN 1943
Temperature Resistance	-40°C to +95°C
Length	5 m, 50 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1260 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	06 December 2021

volzMount 9050L



Applications

- Assembly of mirrors in the manufacture of bedroom, living room, sanitary and wardrobe furniture
- Assembly of PVC window bars
- Assembly of small appliances and hooks on tiles and smooth walls
- Assembly of cable ducts

Benefits

- Extreme resistance to ageing, UV, weathering and plasticisers.
- The backing foam does not yellow and remains permanently elastic
- High initial adhesive strength provides sufficient application safety immediately after assembly
- Vibration-damping and compensating for different expansion coefficients of the joining partners

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 22.12.2024