volzMount 9052



volzMount 9052 has a pressure-sensitive mounting system consisting of a variety of cross-linked, closed-cell PE Foams.

Nominal Values

Backing	PE Foam
Adhesive Type	Synthetic Rubber
Total Thickness	1,000 mm
Color	White (08)
Liner	90 g, white, siliconized Paper
Adhesion to Steel	≥ 20,00 N/25 mm
Tensile Strength	6,00 N/25 mm
Elongation at Break	200%
Shear Strength	> 5000 h
Temperature Resistance	-40°C to +60°C
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	07 June 2021

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzMount 9052



Applications

- Fastening of plastic parts in the automotive, household appliances and machinery industries
- For the assembly of buttons, handles, window grilles and fastening of lettering and badges in the automotive industry

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 25.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com