


volzMount 9076C




volzMount 9076C is a double-sided adhesive tape with a very good final adhesive strength and high temperature resistance. The foam is characterized by its high elongation at break.

Nominal Values

Backing	PE Foam, Black, 180 kg/m ³
Adhesive Type	Solvent Acrylic, Clear
Total Thickness	0,400 mm
Color	Black (04)
Liner	Green, siliconized, PP Film
Adhesion to Steel	20,00 N/25 mm
Tensile Strength	40,00 N/25 mm
Elongation at Break	550%
Shear Strength	> 160 h
Temperature Resistance	-40°C to +100°C
Length	60 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	07 June 2021

volzMount 9076C



Applications

- Mounting of trim, emblems, and mirrors in the automotive industry

Benefits

- Very good final adhesion
- High elongation at the foam break

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 19.04.2025