volzMount 9076C



volzMount 9076C is a double-sided adhesive tape with a very good final adhesive strength and high temperature resistance. The foam is characterized by its high elongation at break.

Nominal Values

Backing	PE Foam, Black, 180 kg/m³
Adhesive Type	Solvent Acrylic, Clear
Total Thickness	0,400 mm
Color	Black (04)
Liner	Green, siliconized, PP Film
Adhesion to Steel	20,00 N/25 mm
Tensile Strength	40,00 N/25 mm
Elongation at Break	550%
Shear Strength	> 160 h
Temperature Resistance	-40°C to +100°C
Length	60 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	07 June 2021

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzMount 9076C



Applications

- Mounting of trim, emblems, and mirrors in the automotive industry

Benefits

- Very good final adhesion
- High elongation at the foam break

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 05.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com