

volzMount V4300 PV1



volzMount V4300 PV1 is a double-sided, self-adhesive tape with a 75 kg/m³, closed-cell, PE-foam carrier and a white, synthetic-rubber adhesive. It has a very aggressive adhesive, high tack, good cohesion, and a high holding power at high and low temperatures.

Nominal Values

Backing	PE Foam, closed-cell, White, 75 kg/m ³
Adhesive Type	Synthetic Rubber, Clear
Total Thickness	1,050 mm
Color	White (08)
Liner	80 g, yellow, bi-siliconized, Paper
Adhesion to Steel	> 14,00 N/25 mm
Tensile Strength	> 31,00 N/25 mm
Elongation at Break	> 190%
Shear Strength	> 2 h
Rolling Ball Tack	< 1,5 cm
Temperature Resistance	-10°C to +60°C
Length	5 m, 33 m, 66 m, 350 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1400 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	17 June 2021

volzMount V4300 PV1



Applications

- Bonding of profiles, frames, nameplates, plastics, emblems
- Suitable for all vertical applications in particular fixing of accessories
- Suitable for permanent fixing of glass and mirrors

Benefits

- Adhesive with good adhesion, high tack and good cohesion even at low and high temperatures
- Resistant to weathering and chemicals
- Good UV resistance
- Very high bond on low surfaces energy substrates

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 30.01.2026