

## volzMount V4302 PV2

volzMount V4302 PV2 is a double-sided, self-adhesive tape with a PE-foam carrier and a white, synthetic-rubber adhesive. It has a very aggressive adhesive, high tack, good cohesion, and a high holding power at high and low temperatures.

### Nominal Values

<b>Backing</b>	PE Foam, closed-cell, White, 100 kg/m <sup>3</sup>
<b>Adhesive Type</b>	Hot Melt, Synthetic Rubber
<b>Total Thickness</b>	1,000 mm
<b>Color</b>	White (08)
<b>Liner</b>	100 g/m <sup>2</sup> ., white, bi-siliconized, Paper
<b>Adhesion to Steel</b>	≥ 10,00 N/25 mm
<b>Shear Strength</b>	≥ 50
<b>Rolling Ball Tack</b>	≤ 8 cm
<b>Temperature Resistance</b>	-10°C to +60°C
<b>Length</b>	5 m, 33 m, 66 m, 300 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1000 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	28 July 2023

## volzMount V4302 PV2

### Applications

- Bonding of profiles, frames, nameplates, plastics, emblems Suitable for all vertical applications in particular fixing of accessories
- Suitable for permanent fixing of glass and mirrors

### Benefits

- Adhesive with good adhesion, high tack and good cohesion even at low and high temperatures
- Resistant to weathering and chemicals
- Good UV resistance
- Very high bond on low surfaces energy substrates

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 17.08.2025