

Technical Product Data Sheet

volzMount V4303 PV1

volzMount V4303 PV1 is a double-sided, self-adhesive tape with a PE-foam carrier and a white, Hotmelt synthetic-rubber adhesive.

Nominal Values

Backing PE Foam (50kg/m³)

Adhesive Type Hotmelt Synthetic Rubber

Total Thickness 2,00 mm

Color White (08)

Liner Yellow, bi-siliconized Paper

Adhesion to Steel 20,00 N/25 mm

Tensile Strength 5 N/12 mm

Elongation at Break 200%

Shear Strength | 20 mm

Temperature Resistance +50°C

Length 25 m, 33 m, 140 m, 145 m, 155 m, other lengths upon request

Width 6 mm, 9 mm, 12 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1000 mm,

other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 24 April 2025















DE-79227 Schallstadt



Technical Product Data Sheet

volzMount V4303 PV1

Applications

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 07.12.2025





DE-79227 Schallstadt



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the





