

## volzMount V4303 PV1

volzMount V4303 PV1 is a double-sided, self-adhesive tape with a PE-foam carrier and a white, Hotmelt synthetic-rubber adhesive.

### Nominal Values

<b>Backing</b>	PE Foam (50kg/m <sup>3</sup> )
<b>Adhesive Type</b>	Hotmelt Synthetic Rubber
<b>Total Thickness</b>	2,00 mm
<b>Color</b>	White (08)
<b>Liner</b>	Yellow, bi-siliconized Paper
<b>Adhesion to Steel</b>	20,00 N/25 mm
<b>Tensile Strength</b>	5 N/12 mm
<b>Elongation at Break</b>	200%
<b>Shear Strength</b>	20 mm
<b>Temperature Resistance</b>	+50°C
<b>Length</b>	25 m, 33 m, 140 m, 145 m, 155 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1000 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	24 April 2025

## volzMount V4303 PV1

### Applications

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 17.06.2026