

## volzMount V5311



volzMount V5311 is a double-sided, self-adhesive tape with a 95 kg/m<sup>3</sup>, closed-cell, PE-foam carrier and a clear, solvent-acrylic adhesive. It has a very aggressive adhesive, high tack, good cohesion, and a high holding power.

### Nominal Values

<b>Backing</b>	PE Foam, closed-cell, White, 95 kg/m <sup>3</sup>
<b>Backing Thickness</b>	0,800 mm
<b>Adhesive Type</b>	Solvent Acrylic, Clear
<b>Total Thickness</b>	0,900 mm
<b>Color</b>	White (08)
<b>Liner</b>	Blue, bi-siliconized, PP Film
<b>Adhesion to Steel</b>	22,50 N/25 mm
<b>Shear Strength</b>	> 168 h
<b>Rolling Ball Tack</b>	□ 10 cm
<b>Temperature Resistance</b>	-30°C to +90°C
<b>Length</b>	66 m, 400 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1220 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	21 February 2022

## volzMount V5311



### Applications

- Bonding of profiles, frames, nameplates, plastics, emblems
- Suitable for all vertical applications in particular fixing of accessories
- Suitable for permanent fixing of glass and mirrors

### Benefits

- Adhesive with good adhesion, high tack and good cohesion even at low and high temperatures
- Resistant to weathering and chemicals
- Good UV resistance

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 15.04.2026