

Technical Product Data Sheet

volzMount V5311



volzMount V5311 is a double-sided, self-adhesive tape with a 95 kg/m³, closed-cell, PE-foam carrier and a clear, solvent-acrylic adhesive. It has a very aggressive adhesive, high tack, good cohesion, and a high holding power.

Nominal Values

Backing PE Foam, closed-cell, White, 95 kg/m³

Backing Thickness 0,800 mm

Adhesive Type Solvent Acrylic, Clear

Total Thickness 0,900 mm

Color White (08)

Liner Blue, bi-siliconized, PP Film

Adhesion to Steel | 22,50 N/25 mm

Shear Strength > 168 h

Rolling Ball Tack | 10 cm

Temperature Resistance -30°C to +90°C

Length 66 m, 400 m, other lengths upon request

Width 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1220

mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 21 February 2022





We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of









DE-79227 Schallstadt



Technical Product Data Sheet

volzMount V5311



Applications

- Bonding of profiles, frames, nameplates, plastics, emblems
- Suitable for all vertical applications in particular fixing of accessories
- Suitable for permanent fixing of glass and mirrors

Benefits

- Adhesive with good adhesion, high tack and good cohesion even at low and high temperatures
- Resistant to weathering and chemicals
- Good UV resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 29.08.2025











