

volzMount V5312



volzMount V5312 is a double-sided, self-adhesive tape with a 95 kg/m³, closed-cell, PE-foam carrier and a solvent-acrylic adhesive. It has a very aggressive adhesive, high tack, good cohesion, and a high holding power.

Nominal Values

Backing	PE Foam, closed-cell, White, 95 kg/m ³
Backing Thickness	0,800 mm
Adhesive Type	Solvent Acrylic, Clear
Total Thickness	0,900 mm
Color	White (08)
Liner	80 g, white, siliconized Paper
Adhesion to Steel	22,50 N/25 mm, (90°)
Shear Strength	168 h
Rolling Ball Tack	< 10 cm
Temperature Resistance	-30°C to +90°C, +120°C (short-term)
Length	66 m, 400 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1220 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	21 February 2022

volzMount V5312



Applications

- Bonding of profiles, frames, nameplates, plastics, emblems
- Suitable for all vertical applications in particular fixing of accessories
- Suitable for permanent fixing of glass and mirrors

Benefits

- Adhesive with good adhesion, high tack and good cohesion
- Resistant to weathering and chemicals
- Good UV resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 29.08.2025