volzMount V5316



volzMount V5316 is a double sided self-adhesive tape which is excellent for mounting nameplates, mirrors, frames, profiles where it is necessary to have high cohesion and high thickness. Essential for outdoor application where U.V. resistance is necessary.

Nominal Values

Backing	PE Foam, closed-cell
Adhesive Type	Acrylic
Total Thickness	1,500 mm
Insulation Class	B 130°C (DIN EN 60085, OANZ2 & OANZ8)
Color	Black (04)
Liner	Blue, bi-siliconized, PP Film
Adhesion to Steel	> 11,25 N/25 mm, (90°), (Foam break)
Shear Strength	> 24 h
Temperature Resistance	-30°C to +100°C
Length	33 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	11 October 2022

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

TAPES
Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzMount V5316



Applications

- Mounting of nameplates, mirrors, frames, profiles
- Essential for outdoor application where it is necessary U.V. resistance

Benefits

- Adhesive with high cohesion & high thickness
- Good UV resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 20°C to 30°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 23.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com