

Technical Product Data Sheet

volzMount V5317



volzMount V5317 is a double-sided, self-adhesive tape with a 75 kg/m³, closed-cell, PE Foam, white carrier and a solvent-acrylic adhesive. It has a very aggressive adhesive, high tack, good cohesion, and a high holding power.

Nominal Values

Backing PE Foam, closed-cell, White, 67 kg/m³

Adhesive Type Solvent Acrylic, Clear

Total Thickness 1,600 mm

> Color White (08)

Liner 80 g, white, bi-siliconized, Paper

Adhesion to Steel > 17,50 N/25 mm

Tensile Strength 20,00 N/25 mm

Elongation at Break > 150%

> **Shear Strength** > 168 h

Rolling Ball Tack < 10 cm

Temperature Resistance -30°C to +90°C

> Length 5 m, 25 m, 33 m, 45 m, 50 m, 300 m, other lengths upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 Width

mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 14 May 2020





DE-79227 Schallstadt



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the











Technical Product Data Sheet

volzMount V5317



Applications

- Bonding of profiles, frames, nameplates, plastics, emblems
- Suitable for all vertical applications in particular fixing of accessories
- Suitable for permanent fixing of glass and mirrors
- Mounting of different materials where it is necessary to have high cohesion and high thickness
- Very good for outdoor use

Benefits

- Adhesive with good adhesion, high tack and good cohesion
- Resistant to weathering and chemicals
- Good UV resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 30.11.2025













DE-79227 Schallstadt