

## volzMount V5317



volzMount V5317 is a double-sided, self-adhesive tape with a 75 kg/m<sup>3</sup>, closed-cell, PE Foam, white carrier and a solvent-acrylic adhesive. It has a very aggressive adhesive, high tack, good cohesion, and a high holding power.

### Nominal Values

<b>Manufacturer</b>	VOLZ®
<b>Backing</b>	PE Foam, closed-cell, White, 67 kg/m <sup>3</sup>
<b>Adhesive Type</b>	Solvent Acrylic, Clear
<b>Total Thickness</b>	1,600 mm
<b>Color</b>	White (08)
<b>Liner</b>	80 g, white, bi-siliconized, Paper
<b>Adhesion to Steel</b>	> 17,50 N/25 mm
<b>Tensile Strength</b>	20,00 N/25 mm
<b>Elongation at Break</b>	> 150%
<b>Shear Strength</b>	> 168 h
<b>Rolling Ball Tack</b>	< 10 cm
<b>Temperature Resistance</b>	-30°C to +90°C
<b>Length</b>	5 m, 25 m, 33 m, 45 m, 50 m, 300 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	14 May 2020

## volzMount V5317



### Applications

- Bonding of profiles, frames, nameplates, plastics, emblems
- Suitable for all vertical applications in particular fixing of accessories
- Suitable for permanent fixing of glass and mirrors
- Mounting of different materials where it is necessary to have high cohesion and high thickness
- Very good for outdoor use

### Benefits

- Adhesive with good adhesion, high tack and good cohesion
- Resistant to weathering and chemicals
- Good UV resistance

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 21.11.2024