

## volzMount V5319



volzMount V5319 is a doubled sided 3,0 mm white, closed cells, low density PE foam coated with a high performance acrylic adhesive system and protected by siliconized paper release liner. Designed for general purpose mounting, assembling of displays, hooks, cable clips, plastic profiles and emblems. High thickness, ideal for applications on rough and irregular surfaces.

### Nominal Values

<b>Backing</b>	PE Foam
<b>Backing Thickness</b>	3,00 mm
<b>Adhesive Type</b>	modified, Acrylic
<b>Total Thickness</b>	3,10 mm
<b>Color</b>	White (08)
<b>Liner</b>	bi-siliconized, Paper
<b>Adhesion to Steel</b>	8,75 N/25 mm, (90°)
<b>Shear Strength</b>	> 168 h
<b>Temperature Resistance</b>	-30°C bis +90°C, 120°C (short-term)
<b>Length</b>	16,5 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	06 July 2021

## volzMount V5319



### Applications

- Mounting of plastic parts in the automotive industry
- Mounting of decorative profiles, furniture trims, electrical conduits
- Mounting of nameplates, emblems and plastic profiles in the building & construction industry

### Benefits

- High initial tack
- Excellent UV and ageing resistance
- Good adhesion to a variety of smooth and rough substrates

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 08.06.2025