

## volzMount V5321



volzMount V5321 is a double-sided, self-adhesive tape with a 70 kg/m<sup>3</sup>, closed-cell, PE-foam carrier and a clear solvent-acrylic adhesive. It has a very aggressive adhesive, high tack, good cohesion, and a high holding power at high and low temperatures.

### Nominal Values

|                               |   |
|-------------------------------|---|
| <b>Backing</b>                | PE Foam, closed-cell, White   |
| <b>Backing Thickness</b>      | 1,000 mm  |
| <b>Adhesive Type</b>          | Solvent Acrylic, Clear  |
| <b>Total Thickness</b>        | 1,100 mm  |
| <b>Color</b>                  | White (08)  |
| <b>Liner</b>                  | white bi-siliconized, Paper   |
| <b>Adhesion to Steel</b>      | 22,50 N/25 mm, ± 10%, (90°)   |
| <b>Tensile Strength</b>       | > 31,00 N/25 mm, ± 10%  |
| <b>Elongation at Break</b>    | 150%  |
| <b>Shear Strength</b>         | 168 h   |
| <b>Rolling Ball Tack</b>      | < 10 cm   |
| <b>Temperature Resistance</b> | -30°C to +90°C, +120°C (short-term)   |
| <b>Length</b>                 | 5 m, 10 m, 50 m, 66 m, 400 m, other lengths upon request  |
| <b>Width</b>                  | 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request |
| <b>Storage Life</b>           | The material can be stored at room temperature for at least 12 months.                          |
| <b>Effective</b>              | 02 March 2026   |

## volzMount V5321



### Applications

- Mounting of plastic parts in the automotive industry
- Mounting of decorative profiles, furniture trims, electrical conduits
- Mounting of nameplates, emblems and plastic profiles in the building & construction industry

### Benefits

- Adhesive with good adhesion, high tack and good cohesion
- Resistant to weathering and chemicals
- Good UV resistance

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 08.07.2026