

# **Technical Product Data Sheet**

## volzMount V5321



volzMount V5321 is a double-sided, self-adhesive tape with a 70 kg/m³, closed-cell, PE-foam carrier and a clea,r solvent-acrylic adhesive. It has a very aggressive adhesive, high tack, good cohesion, and a high holding power at high and low temperatures.

#### **Nominal Values**

**Backing** PE Foam, closed-cell, White, 70 kg/m<sup>3</sup>

**Backing Thickness** 1,000 mm

> **Adhesive Type** Solvent Acrylic, Clear

**Total Thickness** 1,100 mm

> Color White (08)

Liner 80 g, white bi-siliconized, Paper

**Adhesion to Steel** 22,50 N/25 mm, ± 10%, (90°)

**Tensile Strength** > 31,00 N/25 mm, ± 10%

**Elongation at Break** 150%

> **Shear Strength** 168 h

**Rolling Ball Tack** < 10 cm

**Temperature Resistance** -30°C to +90°C, +120°C (short-term)

> Length 5 m, 10 m, 50 m, 66 m, 400 m, other lengths upon request

6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 Width

mm, other widths upon request

**Storage Life** The material can be stored at room temperature for at least 12 months.

**Effective** 26 October 2023





DE-79227 Schallstadt



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of











# **Technical Product Data Sheet**

## volzMount V5321



### **Applications**

- Mounting of plastic parts in the automotive industry
- Mounting of decorative profiles, furniture trims, electrical conduits
- Mounting of nameplates, emblems and plastic profiles in the building & construction industry

#### **Benefits**

- Adhesive with good adhesion, high tack and good cohesion
- Resistant to weathering and chemicals
- Good UV resistance

### **Storage Conditions**

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 17.11.2025











