volzMount V5323 PV4

volzMount V5323 PV4 is a double-sided, self-adhesive tape with a 67 kg/m³, closed-cell, white, PE-foam carrier and a solvent-acrylic adhesive. It has a very aggressive adhesive and a high tack.

Nominal Values

Backing	PE Foam
Adhesive Type	Solvent Acrylic
Total Thickness	0,890 mm
Color	White (08)
Liner	80 gr. blue, PE Film
Adhesion to Steel	≥ 15,00 N/25 mm
Tensile Strength	118,25 N/25 mm
Rolling Ball Tack	≤ 7 cm
Length	66 m, 350 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1200 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Density	67kg/m³
Effective	12 February 2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

TAPES
Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzMount V5323 PV4

Applications

- Bonding of profiles, frames, nameplates, profiles, emblems & plastics
- Suitable for all vertical applications in particular fixing of accessories
- Suitable for permanent fixing of glass and mirrors
- Used as sound insulation and vibration control in automotive and industrial equipment

Benefits

- Adhesive with good adhesion, high tack and good cohesion
- Resistant to weathering and chemicals
- Good UV resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 22.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com