

volzMount V5323 PV4

volzMount V5323 PV4 is a double-sided, self-adhesive tape with a 67 kg/m³, closed-cell, white, PE-foam carrier and a solvent-acrylic adhesive. It has a very aggressive adhesive and a high tack.

Nominal Values

Backing	PE Foam
Adhesive Type	Solvent Acrylic
Total Thickness	0,890 mm
Color	White (08)
Liner	80 gr. blue, PE Film
Adhesion to Steel	≥ 15,00 N/25 mm
Tensile Strength	118,25 N/25 mm
Rolling Ball Tack	≤ 7 cm
Length	66 m, 350 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1200 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Density	67kg/m ³
Effective	12 February 2026

volzMount V5323 PV4

Applications

- Bonding of profiles, frames, nameplates, profiles, emblems & plastics
- Suitable for all vertical applications in particular fixing of accessories
- Suitable for permanent fixing of glass and mirrors
- Used as sound insulation and vibration control in automotive and industrial equipment

Benefits

- Adhesive with good adhesion, high tack and good cohesion
- Resistant to weathering and chemicals
- Good UV resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 25.05.2026