

Technical Product Data Sheet

volzMount V5324



volzMount V5324 is a double-sided, self-adhesive tape with a 67 kg/m³, closed-cell, PE-foam carrier and a clear solventacrylic adhesive. It has a very aggressive adhesive and a high tack.

Nominal Values

Rolling Ball Tack

Effective

23 March 2021



DE-79227 Schallstadt





We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the











Technical Product Data Sheet

volzMount V5324



Applications

- Bonding of profiles, frames, nameplates, profiles, emblems & plastics
- Suitable for all vertical applications in particular fixing of accessories
- accessories Suitable for permanent fixing of glass and mirrors
- Used as sound insulation and vibration control in automotive and industrial equipment

Benefits


- Adhesive with good adhesion, high tack and good cohesion
- Resistant to weathering and chemicals
- Good UV resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 08.08.2025















DE-79227 Schallstadt