

volzMount V5324



volzMount V5324 is a double-sided, self-adhesive tape with a 67 kg/m³, closed-cell, PE-foam carrier and a clear solvent-acrylic adhesive. It has a very aggressive adhesive and a high tack.

Nominal Values

| | |
|-------------------------------|---|
| Backing | PE Foam, closed-cell, 67 kg/m ³ |
| Adhesive Type | Solvent Acrylic |
| Total Thickness | 1,000 mm |
| Color | White (08), Black (04) |
| Liner | Red, bi-siliconized, PP Film |
| Adhesion to Steel | > 14,00 N/25 mm |
| Tensile Strength | > 23,00 N/25 mm |
| Elongation at Break | > 219% |
| Shear Strength | 2 h, (± 10%) |
| Rolling Ball Tack | < 2 cm |
| Temperature Resistance | -20°C to +90°C |
| Length | 66 m, 350 m, other lengths upon request |
| Width | 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1200 mm, other widths upon request |
| Storage Life | The material can be stored at room temperature for at least 12 months. |
| Effective | 23 March 2021 |

volzMount V5324



Applications

- Bonding of profiles, frames, nameplates, profiles, emblems & plastics
- Suitable for all vertical applications in particular fixing of accessories
- accessories Suitable for permanent fixing of glass and mirrors
- Used as sound insulation and vibration control in automotive and industrial equipment

Benefits

- Adhesive with good adhesion, high tack and good cohesion
- Resistant to weathering and chemicals
- Good UV resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 13.12.2025