

volzMount V5327

volzMount V5327 is a black, double-sided, 3,0 mm black, PE foam adhesive tape with a solvent acrylic adhesive.

Nominal Values

Backing	PE Foam (50kg/m ³)
Adhesive Type	Solvent Acrylic
Total Thickness	3,00 mm
Color	Black (04)
Liner	red PE Film
Adhesion to Steel	≥ 16,00 N/25 mm
Shear Strength	≤ 0,50 mm
Rolling Ball Tack	≤ 4 cm
Length	200 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 19 mm, 1030 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	14 August 2025

volzMount V5327

Applications

- Mounting of plastic parts in the automotive industry
- Mounting of decorative profiles, furniture trims, electrical conduits
- Mounting of nameplates, emblems and plastic profiles in the building & construction industry

Benefits

- Good initial tack and shear strength
- Strong adhesion to a variety of smooth and rough substrates

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 29.01.2026