

## volzMount V5327

volzMount V5327 is a black, double-sided, 3,0 mm black, PE foam adhesive tape with a solvent acrylic adhesive.

### Nominal Values

<b>Backing</b>	PE Foam (50kg/m <sup>3</sup> )
<b>Adhesive Type</b>	Solvent Acrylic
<b>Total Thickness</b>	3,00 mm
<b>Color</b>	Black (04)
<b>Liner</b>	red PE Film
<b>Adhesion to Steel</b>	≥ 16,00 N/25 mm
<b>Shear Strength</b>	≤ 0,50 mm
<b>Rolling Ball Tack</b>	≤ 4 cm
<b>Length</b>	200 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 19 mm, 1030 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	14 August 2025

## volzMount V5327

### Applications

- Mounting of plastic parts in the automotive industry
- Mounting of decorative profiles, furniture trims, electrical conduits
- Mounting of nameplates, emblems and plastic profiles in the building & construction industry

### Benefits

- Good initial tack and shear strength
- Strong adhesion to a variety of smooth and rough substrates

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 25.04.2026