volzMount V5331



volzMount V5331 is a double-sided, closed-cell, medium density, PE-foam coated with a high-performance acrylic adhesive, protected by a siliconized PE-release liner. Designed for glazing applications, mounting and assembling of body side mouldings, emblems, mirrors, labels, etc. Plastic liner for easy removal.

Nominal Values

Backing	PE Foam, closed-cell, Black, 85 kg/m³
Backing Thickness	0,800 mm
Adhesive Type	Solvent Acrylic, Clear
Total Thickness	0,900 mm
Color	Black (04)
Liner	Green, bi-siliconized, PE Film
Adhesion to Steel	17,50 N/25 mm
Shear Strength	> 168 h
Rolling Ball Tack	< 10 cm
Temperature Resistance	-30°C to +90°C
Length	66 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1220 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	28 November 2021

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

TAPES
Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzMount V5331



Applications

- Mounting of plastic parts, body side mouldings and emblems in the automotive industry
- Mounting of decorative profiles in the furniture industry
- Assembling of double glazing in the building and construction industry

Benefits

- High initial tack and shear strength
- Excellent UV and ageing resistance

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 25.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com