

## volzMount V5341



volzMount V5341 is a double sided self-adhesive tape with a 3mm closed cell, low density white PE foam carrier coated with a high performance rubber adhesive system and protected by siliconized paper release liner. Designed for general purpose mounting, assembling of displays, hooks, cable clips, plastic profiles, poster, etc. High thickness, ideal for applications on rough and irregular surfaces.

## Nominal Values

<b>Backing</b>	PE Foam
<b>Backing Thickness</b>	3,000 mm
<b>Adhesive Type</b>	Synthetic Rubber
<b>Total Thickness</b>	3,100 mm
<b>Color</b>	White (08)
<b>Liner</b>	bi-siliconized, Paper
<b>Adhesion to Steel</b>	10,00 N/25 mm, (90°)
<b>Shear Strength</b>	≥ 168 h
<b>Rolling Ball Tack</b>	< 10 cm
<b>Temperature Resistance</b>	-10°C bis +70°C, -10°C bis +100°C (short-term)
<b>Length</b>	16,5 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	24 March 2022

# volzMount V5341



## Applications

- Mounting of plastic parts in automotive and home appliance industry
- Mounting of decorative profiles, furniture trims, electrical conduits
- Mounting of nameplates, emblems and plastic profiles in the building and construction industry

## Benefits

- High initial tack
- Good adhesion to a variety of smooth and rough substrates
- Good ageing resistance

## Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 05.02.2026