

## volzMount V5343



volzMount V5343 is a double sided self-adhesive tape with a 3mm closed cell, low density Black (04) PE foam carrier coated with a high performance acrylic adhesive system and protected by siliconized paper release liner. Designed for glazing applications, good adhesion and initial tack on glass, wood, aluminium, etc.

## Nominal Values

<b>Backing</b>	PE Foam
<b>Backing Thickness</b>	3,000 mm
<b>Adhesive Type</b>	modified, Solvent Acrylic
<b>Total Thickness</b>	3,100 mm
<b>Color</b>	Black (04)
<b>Liner</b>	bi-siliconized, Paper
<b>Adhesion to Steel</b>	10,00 N/25 mm, (90°)
<b>Shear Strength</b>	168 h
<b>Rolling Ball Tack</b>	< 10 cm
<b>Temperature Resistance</b>	-30°C to +90°C, -30°C to +120°C (short-term)
<b>Length</b>	16,5 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1500 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	17 January 2022

# volzMount V5343



## Applications

- Mounting of plastic parts in automotive and home appliance industry
- Mounting of decorative profiles, furniture trims, electrical conduits
- Mounting of nameplates, emblems and plastic profiles in the building and construction industry

## Benefits

- High initial tack
- Good adhesion to a variety of smooth and rough substrates
- Good ageing resistance

## Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 19°C to 21°C, with a relative humidity of 50%. When using an adhesive tape stored below 19°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 16.01.2026