

## volzMount V5346 PV2

volzMount V5346 PV2 is 1,0 mm white, medium density PE foam coated with a high-performance rubber adhesive system and protected by siliconized paper release liner. Designed for general purpose mounting, assembling of displays, hooks, cable clips, plastic profiles, emblems.

### Nominal Values

<b>Backing</b>	PE Foam, closed-cell, White, 67 kg/m <sup>3</sup>
<b>Adhesive Type</b>	Solvent Rubber, Clear
<b>Total Thickness</b>	1,000 mm
<b>Color</b>	White (08)
<b>Liner</b>	90 g/m <sup>2</sup> , white, bi-siliconized, Paper
<b>Adhesion to Steel</b>	9,81 N/25 mm
<b>Temperature Resistance</b>	-10°C to +70°C
<b>Length</b>	33 m, 300 m, other lengths upon request
<b>Width</b>	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1000 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	22 November 2023

## volzMount V5346 PV2

### Applications

- Used as sound insulation and vibration control in automotive and industrial equipment
- Suitable as wrapping for electronic components, gaskets, etc.
- Mounting of material such as profiles, wood, plastic, metal, rubber, EPDM, etc. where it is necessary to have a high tack

### Benefits

- Adhesive with aggressive, high tack to high cohesion
- Good resistance against humidity, mild acids, oils, and fats

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 02.05.2026