

# **Technical Product Data Sheet**

## volzMount V5346

volzMount V5346 is a 1,0 mm white, medium density PE foam coated with a high-performance rubber adhesive system and protected by siliconized paper release liner. Designed for general purpose mounting, assembling of displays, hooks, cable clips, plastic profiles, emblems.

#### **Nominal Values**

**Backing** PE Foam, closed-cell, White, 67 kg/m<sup>3</sup>

**Adhesive Type** Solvent Rubber, Clear

**Total Thickness** 1,000 mm

> Color White (08)

Liner 90 g/m<sup>2</sup>, brown, bi-siliconized, Paper

**Adhesion to Steel** 9.81 N/25 mm

**Temperature Resistance** -10°C to +70°C

> Length 33 m, 300 m, other lengths upon request

Width 6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1000

mm, other widths upon request

**Storage Life** The material can be stored at room temperature for at least 12 months.

**Effective** 22 November 2023







We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the







DE-79227 Schallstadt



# **Technical Product Data Sheet**

# volzMount V5346

### **Applications**

- Used as sound insulation and vibration control in automotive and industrial equipment
- Suitable as wrapping for electronic components, gaskets, etc.
- Mounting of material such as profiles, wood, plastic, metal, rubber, EPDM, etc. where it is necessary to have a high tack

#### **Benefits**

- Adhesive with aggressive, high tack to high cohesion
- Good resistance against humidity, mild acids, oils, and fats

## **Storage Conditions**

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 26.11.2025







We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the







