

volzMount V5346

volzMount V5346 is a 1,0 mm white, medium density PE foam coated with a high-performance rubber adhesive system and protected by siliconized paper release liner. Designed for general purpose mounting, assembling of displays, hooks, cable clips, plastic profiles, emblems.

Nominal Values

Backing	PE Foam, closed-cell, White, 67 kg/m ³
Adhesive Type	Solvent Rubber, Clear
Total Thickness	1,000 mm
Color	White (08)
Liner	90 g/m ² , brown, bi-siliconized, Paper
Adhesion to Steel	9,81 N/25 mm
Temperature Resistance	-10°C to +70°C
Length	33 m, 300 m, other lengths upon request
Width	6 mm, 9 mm, 12 mm, 15 mm, 19 mm, 25 mm, 30 mm, 38 mm, 50 mm, 1000 mm, other widths upon request
Storage Life Effective	The material can be stored at room temperature for at least 12 months. 22 November 2023

volzMount V5346

Applications

- Used as sound insulation and vibration control in automotive and industrial equipment
- Suitable as wrapping for electronic components, gaskets, etc.
- Mounting of material such as profiles, wood, plastic, metal, rubber, EPDM, etc. where it is necessary to have a high tack

Benefits

- Adhesive with aggressive, high tack to high cohesion
- Good resistance against humidity, mild acids, oils, and fats

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 25.05.2026