

# **Technical Product Data Sheet**

## volzPack 1020

volzPack 1020 is a packaging tape with a natural rubber adhesive on a PVC film. The tape is printable and also available as a machine roll.

#### **Nominal Values**

**Backing PVC Film** 

**Backing Thickness** 0,032 mm (± 10%)

**Adhesive Type** Natural Rubber

**Total Thickness** 0,051 mm (± 10%)

> Color Brown (79), White (08), Clear (00)

**Adhesion to Steel** 6,00 N/25 mm

**Tensile Strength** 117,50 N725 mm

**Elongation at Break** 60%

**Temperature Resistance** +10°C to +45°C (Application), -25°C to +65°C (Service)

> Length 66 m, 1000 m, other lengths upon request

66 m: 12 mm, 15 mm, 19 mm, 25 mm, 38 mm, 50 mm, 75 mm Width

> 1000 m: 50 mm, 75 mm Other widths by request

**Storage Life** The material can be stored at room temperature for at least 12 months.

**Effective** 20 February 2024















DE-79227 Schallstadt



# **Technical Product Data Sheet**

## volzPack 1020

### **Applications**

- · Suitable for all types of packaging
- Ideal for storage at extreme temperatures and high humidity

#### **Benefits**

- Good adhesion even in recycled cartons
- Long lasting adhesive strength
- Printable with vinyl inks
- Excellent tack
- · Easy and quiet unwinding

### **Storage Conditions**

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 27.07.2025







We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the







