

Technical Product Data Sheet

volzPack 1020

volzPack 1020 is a packaging tape with a natural rubber adhesive on a PVC film. The tape is printable and also available as a machine roll.

Nominal Values

Backing PVC Film

Backing Thickness 0,032 mm (± 10%)

Adhesive Type Natural Rubber

Total Thickness 0,051 mm (± 10%)

> Color Brown (79), White (08), Clear (00)

Adhesion to Steel 6,00 N/25 mm

Tensile Strength 117,50 N725 mm

Elongation at Break 60%

Temperature Resistance +10°C to +45°C (Application), -25°C to +65°C (Service)

> Length 66 m, 1000 m, other lengths upon request

66 m: 12 mm, 15 mm, 19 mm, 25 mm, 38 mm, 50 mm, 75 mm Width

> 1000 m: 50 mm, 75 mm Other widths by request

The Rolls should be stored in their packaging protected from light and at a **Storage Life**

> temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the

tape at room temperature for 24 hours to preserve its characteristics.

Effective 20 February 2024















DE-79227 Schallstadt



Technical Product Data Sheet

volzPack 1020

Applications

- Suitable for all types of packaging
- Ideal for storage at extreme temperatures and high humidity

Benefits

- Good adhesion even in recycled cartons
- Long lasting adhesive strength
- Printable with vinyl inks
- Excellent tack
- Easy and quiet unwinding


Storage Conditions

The material can be stored at room temperature for at least 12 months.

Print Date: 16.04.2025







DE-79227 Schallstadt



We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the









standard processing guidelines for adhesive tapes, which we will gladly send you upon request.