volzPack 1020

volzPack 1020 is a packaging tape with a natural rubber adhesive on a PVC film. The tape is printable and also available as a machine roll.

Nominal Values

Backing	PVC Film
Backing Thickness	0,032 mm (± 10%)
Adhesive Type	Natural Rubber
Total Thickness	0,051 mm (± 10%)
Color	Brown (79), White (08), Clear (00)
Adhesion to Steel	6,00 N/25 mm
Tensile Strength	117,50 N725 mm
Elongation at Break	60%
Temperature Resistance	+10°C to +45°C (Application), -25°C to +65°C (Service)
Length	66 m, 1000 m, other lengths upon request
Width	66 m: 12 mm, 15 mm, 19 mm, 25 mm, 38 mm, 50 mm, 75 mm 1000 m: 50 mm, 75 mm Other widths by request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	20 February 2024

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzPack 1020

Applications

- Suitable for all types of packaging
- Ideal for storage at extreme temperatures and high humidity

Benefits

- Good adhesion even in recycled cartons
- Long lasting adhesive strength
- Printable with vinyl inks
- Excellent tack
- Easy and quiet unwinding

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 26.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com