

volzPack 2080

volzPack 2080 is a standard packaging tape equipped with a Hotmelt adhesive. It is a packaging tape for manual application with dispensers. Also suitable for machine application.

Nominal Values

| | |
|-------------------------------|--|
| Backing | BOPP Film |
| Backing Thickness | 0,025 mm |
| Adhesive Type | Hotmelt Synthetic Rubber |
| Total Thickness | 0,042 mm |
| Color | Brown (79), White (08), Clear (00) |
| Adhesion to Steel | 13,00 N/25 mm |
| Tensile Strength | 95,00 N/25 mm |
| Elongation at Break | 130% |
| Shear Strength | 6 h* |
| Temperature Resistance | #BEZUG! |
| Length | 60 m, other lengths upon request |
| Width | 48 mm, other widths upon request |
| Storage Life | The material can be stored at room temperature for at least 12 months. |
| Additional Info | *To kraft paper at 50°C in oven |
| Effective | 20 March 2025 |

volzPack 2080

Applications

- Universally applicable for light weight packaging
- Suitable for recycled cartons
- Manual and automatic sealing of cartons

Benefits

- Strong initial tack
- The high bond strength of the adhesive ensures permanent adhesion and safe storage, even in fluctuating temperatures
- Excellent adhesive strength even in recycled cartons

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 29.01.2026