

Technical Product Data Sheet

volzPack 2080

volzPack 2080 is a standard packaging tape equipped with a Hotmelt adhesive. It is a packaging tape for manual application with dispensers. Also suitable for machine application.

Nominal Values

Backing BOPP Film

Backing Thickness 0,025 mm

Adhesive Type Hotmelt Synthetic Rubber

Total Thickness 0,042 mm

Color Brown (79), White (08), Clear (00)

Adhesion to Steel | 13,00 N/25 mm

Tensile Strength 95,00 N/25 mm

Elongation at Break 130%

Shear Strength 6 h*

Temperature Resistance | +6°C to +45°C (Application), -10°C to +60°C (Service)

Length 60 m, other lengths upon request

Width 48 mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Additional Info *To kraft paper at 50°C in oven

Effective 20 March 2025















DE-79227 Schallstadt



Technical Product Data Sheet

volzPack 2080

Applications

- Universally applicable for light weight packaging
- Suitable for recycled cartons
- Manual and automatic sealing of cartons

Benefits

- Strong initial tack
- The high bond strength of the adhesive ensures permanent adhesion and safe storage, even in fluctuating
- Excellent adhesive strength even in recycled cartons

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 13.11.2025







We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of







