

volzPack 2080

volzPack 2080 is a standard packaging tape equipped with a Hotmelt adhesive. It is a packaging tape for manual application with dispensers. Also suitable for machine application.

Nominal Values

Backing	BOPP Film
Backing Thickness	0,025 mm
Adhesive Type	Hotmelt Synthetic Rubber
Total Thickness	0,042 mm
Color	Brown (79), White (08), Clear (00)
Adhesion to Steel	13,00 N/25 mm
Tensile Strength	95,00 N/25 mm
Elongation at Break	130%
Shear Strength	6 h*
Temperature Resistance	+6°C to +45°C (Application), -10°C to +60°C (Service)
Length	60 m, other lengths upon request
Width	48 mm, other widths upon request
Storage Life	The material can be stored at room temperature for at least 12 months.
Additional Info	*To kraft paper at 50°C in oven
Effective	20 March 2025

volzPack 2080

Applications

- Universally applicable for light weight packaging
- Suitable for recycled cartons
- Manual and automatic sealing of cartons

Benefits

- Strong initial tack
- The high bond strength of the adhesive ensures permanent adhesion and safe storage, even in fluctuating temperatures
- Excellent adhesive strength even in recycled cartons

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 14.04.2026