

## volzPack 2080

volzPack 2080 is a standard packaging tape equipped with a Hotmelt adhesive. It is a packaging tape for manual application with dispensers. Also suitable for machine application.

### Nominal Values

<b>Backing</b>	BOPP Film
<b>Backing Thickness</b>	0,025 mm
<b>Adhesive Type</b>	Hotmelt Synthetic Rubber
<b>Total Thickness</b>	0,042 mm
<b>Color</b>	Brown (79), White (08), Clear (00)
<b>Adhesion to Steel</b>	13,00 N/25 mm
<b>Tensile Strength</b>	95,00 N/25 mm
<b>Elongation at Break</b>	130%
<b>Shear Strength</b>	6 h*
<b>Temperature Resistance</b>	+6°C to +45°C (Application), -10°C to +60°C (Service)
<b>Length</b>	60 m, other lengths upon request
<b>Width</b>	48 mm, other widths upon request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Additional Info</b>	*To kraft paper at 50°C in oven
<b>Effective</b>	20 March 2025

## volzPack 2080

### Applications

- Universally applicable for light weight packaging
- Suitable for recycled cartons
- Manual and automatic sealing of cartons

### Benefits

- Strong initial tack
- The high bond strength of the adhesive ensures permanent adhesion and safe storage, even in fluctuating temperatures
- Excellent adhesive strength even in recycled cartons

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 12.04.2026