

## volzPack 3013 PV2

volzPack 3013 PV2 is a self-adhesive kraft tape with a hotmelt, synthetic rubber adhesive with hydrocarbon resins. The tape is suitable for manual and automated applications. It has excellent adhesion, even on boxes made from recycled paper.

### Nominal Values

|                               |  |
|-------------------------------|--|
| <b>Backing</b>                | Paper  |
| <b>Backing Thickness</b>      | 0,090 mm   |
| <b>Adhesive Type</b>          | Hotmelt Synthetic Rubber   |
| <b>Total Thickness</b>        | 0,110 mm   |
| <b>Color</b>                  | Brown (15)   |
| <b>Adhesion to Steel</b>      | 21,25 N/25 mm  |
| <b>Tensile Strength</b>       | 112,50 N/25 mm   |
| <b>Shear Strength</b>         | 100 h  |
| <b>Temperature Resistance</b> | #BEZUG!  |
| <b>Length</b>                 | 50 m, 400 m, 500m, other lengths upon request                          |
| <b>Width</b>                  | 50 mm, 75 mm, Other widths by request                                  |
| <b>Storage Life</b>           | The material can be stored at room temperature for at least 12 months. |
| <b>Effective</b>              | 09 January 2025  |

# volzPack 3013 PV2

## Applications

- Kraft paper carton sealing tape suitable for manual and automated application.

## Benefits

- Excellent adhesion even in recycled cartons
- Good tack
- Printable
- Hand tearable

## Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 29.01.2026