volzPack 3013 PV2

volzPack 3013 PV2 is a self-adhesive kraft tape with a hotmelt, synthetic rubber adhesive with hydrocarbon resins. The tape is suitable for manual and automated applications. It has excellent adhesion, even on boxes made from recycled paper.

Nominal Values

Backing	Paper
Backing Thickness	0,090 mm
Adhesive Type	Hotmelt Synthetic Rubber
Total Thickness	0,110 mm
Color	Brown (15)
Adhesion to Steel	21,25 N/25 mm
Tensile Strength	112,50 N/25 mm
Shear Strength	100 h
Temperature Resistance	+6°C to +45°C (Application), -10°C to +60°C (Service)
Length	50 m, 400 m, 500m, other lengths upon request
Width	50 mm, 75 mm, Other widths by request
Storage Life	The material can be stored at room temperature for at least 12 months.
Effective	09 January 2025

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com

volzPack 3013 PV2

Applications

- Kraft paper carton sealing tape suitable for manual and automated application.

Benefits

- Excellent adhesion even in recycled cartons
- Good tack
- Printable
- Hand tearable

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 05.11.2026

We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the standard processing guidelines for adhesive tapes, which we will gladly send you upon request.

Volz Selbstklebetecknik GmbH
Fischerinsel 3
DE-79227 Schallstadt
Phone: +49 (0)7664 50500-0
Fax: +49 (0)7664 50500-50
info@volztapes.com
www.volztapes.com