

## volzPack 3013 PV2

volzPack 3013 PV2 is a self-adhesive kraft tape with a hotmelt, synthetic rubber adhesive with hydrocarbon resins. The tape is suitable for manual and automated applications. It has excellent adhesion, even on boxes made from recycled paper.

### Nominal Values

<b>Backing</b>	Paper
<b>Backing Thickness</b>	0,090 mm
<b>Adhesive Type</b>	Hotmelt Synthetic Rubber
<b>Total Thickness</b>	0,110 mm
<b>Color</b>	Brown (15)
<b>Adhesion to Steel</b>	21,25 N/25 mm
<b>Tensile Strength</b>	112,50 N/25 mm
<b>Shear Strength</b>	100 h
<b>Temperature Resistance</b>	+6°C to +45°C (Application), -10°C to +60°C (Service)
<b>Length</b>	50 m, 400 m, 500m, other lengths upon request
<b>Width</b>	50 mm, 75 mm, Other widths by request
<b>Storage Life</b>	The material can be stored at room temperature for at least 12 months.
<b>Effective</b>	09 January 2025

## volzPack 3013 PV2

### Applications

- Kraft paper carton sealing tape suitable for manual and automated application.

### Benefits

- Excellent adhesion even in recycled cartons
- Good tack
- Printable
- Hand tearable

### Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 29.08.2025