

Technical Product Data Sheet

volzPack 3013 PV7

volzPack 3013 PV7 is packaging tape consisting of saturated crepe paper with a natural rubber and hydrocarbon resin adhesive. It has excellent tack with good, long lasting adhesion, even on boxes made from recycled paper. It is ideal for storage in extreme temperature conditions and high moisture environments.

Nominal Values

Backing Saturated Crepe Paper

Backing Thickness 0,090 mm

> **Adhesive Type** Natural rubber and Hydrocarbon Resins

Total Thickness 0,125 mm

> Color Brown (15)

Adhesion to Steel 6,25 N/25 mm

Tensile Strength 125,00 N/25 mm

Temperature Resistance +2°C to +45°C (Application), -25°C to +65°C (Service)

> Length 50 m, other lengths upon request

Width 50 mm, 1500 mm, other widths upon request

Storage Life The material can be stored at room temperature for at least 12 months.

Effective 03 April 2025







We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of











Technical Product Data Sheet

volzPack 3013 PV7

Applications

Packaging tape for cardboard boxes

Benefits

- Good adhesion even in recycled cartons
- Excellent tack
- Long lasting adhesion
- Ideal for storage in extreme temperature conditions and high moisture environments
- Printable
- Hand tearable

Storage Conditions

The Rolls should be stored in their packaging protected from light and at a temperature between 15°C to 24°C, with a relative humidity of 50% +/- 30%. When using an adhesive tape stored below 15°C, it is advisable to keep the tape at room temperature for 24 hours to preserve its characteristics.

Print Date: 02.08.2025









We provide the technical data of our products to the best of our knowledge, but without obligation. Due to the wide range of material and environmental influences, we recommend a suitability test on original products prior to use. Please also note the







