

Art. No.	Description	Thickness	Applications	Sample
4750-0 ⁽¹⁾ PUR Ester 42 kg/m ³ Grey (55)	<ul style="list-style-type: none"> Open-cell sealing tape with PET-film intermediate carrier for over expansion protection Mod. water based acrylic adhesive Perm. temperature resistance 120°C 	4751-0: 3 mm 4752-0: 4 mm 4753-0: 6 mm 4754-0: 5 mm 4755-0: 9 mm 4756-0: 12 mm	<ul style="list-style-type: none"> Sealing tape in luminaries Sealing tape for soft storage and sealing of goods Soft storage of electrical, acoustics, and measuring devices Acoustic and sound insulation 	
4760-0 ⁽¹⁾ PUR Ester 42 kg/m ³ Black (04) White (08)	<ul style="list-style-type: none"> Open-cell sealing tape with PET-film intermediate carrier for over expansion protection Mod. water based acrylic adhesive 	4761-0: 3 mm 4763-0: 6 mm 4765-0: 9 mm 4766-0: 12 mm	<ul style="list-style-type: none"> Sealing tape against drafts, dust etc. Sealing of formwork joints for exposed (fair-faced) concrete Soft storage of sensitive components Protection against vibration on machines and devices 	
1890-0 ⁽¹⁾ PUR Ester 28 kg/m ³ Black (04) White (08)	<ul style="list-style-type: none"> Open-celled sealing tape with PET-film intermediate carrier for over expansion protection Mod. water based acrylic adhesive 	1891-0: 3 mm 1892-0: 4 mm 1893-0: 6 mm 1894-0: 8 mm 1895-0: 9 mm 1896-0: 10 mm 1897-0: 12 mm	<ul style="list-style-type: none"> Sealing tape against drafts, dust etc. Sealing in lighting and window construction industries Acoustic and sound insulation Shock-absorbing, sealing tape Protection against vibration on machines and devices 	
60490-1 ⁽¹⁾ EPDM 130 kg/m ³ Black (04)	<ul style="list-style-type: none"> Closed-cell sealing tape with fleece carrier for over expansion protection Mod. water based acrylic adhesive Weather, age, and UV resistant Resistant to a variety of organic and inorganic solvents 	60490-1: 2 mm 60491-1: 3 mm 60492-1: 4 mm 60493-1: 6 mm 60494-1: 8 mm 60495-1: 5 mm 60496-1: 10 mm 60497-1: 15 mm 60499-1: 1 mm	<ul style="list-style-type: none"> Sealing tape against drafts, dust, moisture etc. Sealing of electrical cabinets and electrical machines Protection against vibration on machines and devices Acoustic and sound insulation of speakers Gaskets, underlays and die-cuts for the automotive industry 	
1720 ⁽¹⁾ APTK 170 kg/m ³ Black (04)	<ul style="list-style-type: none"> Closed-cell sealing tape without any intermediate carrier Mod. water based acrylic adhesive Weather, age, and UV resistant Resistant to a variety of organic and inorganic solvents 	1720: 2 mm 1721: 3 mm 1722: 4 mm 1723: 6 mm 1724: 8 mm 1725: 5 mm 1726: 10 mm 1727: 12 mm	<ul style="list-style-type: none"> Sealing tape against drafts, dust, moisture, etc. Sealing of electrical cabinets and electrical machines Protection against vibration on machines and devices Acoustic and sound insulation of speakers Gaskets, underlays and die-cuts for the automotive industry 	
1710 ⁽¹⁾ PE 30 kg/m ³ Black (04) White (08)	<ul style="list-style-type: none"> Closed-cell sealing tape without any intermediate carrier Hotmelt adhesive Weather, age, and UV resistant Resistant to a variety of organic and inorganic solvents, alkalis, and acids 	1710: 2 mm 1711: 3 mm 1712: 4 mm 1713: 5 mm 1714: 6 mm 1715: 8 mm 1716: 10 mm	<ul style="list-style-type: none"> Window tape Sealing of air-conditioning ducts, dome lights, solar power systems, ventilation, mechanical and apparatus construction Secure sealing of structural parts on walls, ceilings and floors Sealing of formwork joints for exposed (fair-faced) concrete Impact sound and vibration insulation 	
2710 ⁽¹⁾ PE 30 kg/m ³ Black (04) White (08)	<ul style="list-style-type: none"> Closed-cell sealing tape with a laminated film on the back of the foam Hotmelt adhesive Weather, age, and UV resistant Resistant to a variety of organic and inorganic solvents, alkalis, and acids 	2710: 2 mm 2711: 3 mm 2712: 4 mm 2713: 5 mm 2714: 6 mm 2715: 8 mm 2716: 10 mm	<ul style="list-style-type: none"> Window tape Secure sealing of structural parts on walls, ceilings and floors Prefabrication of partition wall panels Impact sound insulation in partition wall construction Sealing in ventilation, mechanical and apparatus engineering 	
1700 ⁽¹⁾ PVC 160 kg/m ³ Light grey (18)	<ul style="list-style-type: none"> Closed-cell sealing tape without any intermediate carrier Mod. water based acrylic adhesive Weather, age, and UV resistant Very flexible and conformable 	1700: 2 mm 1701: 3 mm 1702: 4 mm 1703: 5 mm 1704: 6 mm	<ul style="list-style-type: none"> Sealing in air-conditioning and exhaust systems Stacking intermediate layer for the glass industry Transport protection of metal, plastic, and wood panels 	
4700-1 ⁽¹⁾ PVC 200 kg/m ³ White (08)	<ul style="list-style-type: none"> Closed-cell sealing tape with fleece carrier for over expansion protection Mod. water based acrylic adhesive Weather, age, and UV resistant Resistant to a variety of organic and inorganic solvents, alkalis, acids, etc. 	4700-1: 2 mm 4702-1: 4 mm	<ul style="list-style-type: none"> Sealing tape against dust and moisture in electrical devices, such as refrigerators, washing machines, dishwashers, etc. Noise and rattle protection in vehicle, housing and ship construction Stacking intermediate layer in the glass industry Transport protection of metal, plastic, and wood, plates 	
1741/-93 EPDM 280 kg/m ³ White (08)	<ul style="list-style-type: none"> Closed-cell sealing profile, scrim reinforced for over expansion protection Hotmelt Adhesive Age and UV resistant, chemically neutral 	1741: K-profile 1793: P-profile 1741: 3,5 mm 1793: 5,5 mm	<ul style="list-style-type: none"> Sealing tape against acid, alkalis, solvents, and other aggressive chemicals Sealing tape in green house and window industries Sealing tape in aerospace, automotive, etc. 	
25810 ⁽¹⁾ Keratape 300 kg/m ³ White (08)	<ul style="list-style-type: none"> Single sided, self-adhesive, asbestos-free, high-temperature, fibre-glass tape with fleece intermediate carrier Mod. water based acrylic adhesive Max. operating temperature 1100° 	25810: 2 mm 25811: 3 mm 25812: 4 mm 25813: 5 mm 25814: 6 mm	<ul style="list-style-type: none"> Used in high temperature applications Sealing tape for special fire code protections and other security requirements Non-cancerous 	
51130/31 PUR 150 kg/m ³ Black (04)	<ul style="list-style-type: none"> Impregnated PUR flexible foam Acrylic adhesive with flame retardant additives Compliant with DIN 18542 BG1 (51130) / BG2 (51131) Vapour permeability 	on request	<ul style="list-style-type: none"> Sealing of acoustic noise, driving rain, dust, drafts, splash water, and loss of heat Sealing tape in facade construction, drywall and metal construction 51130 = Sealing up to 600 PA (Wind speed Bft. 11) 51131 = Sealing up to 300 PA (Wind speed Bft. 9) 	

Custom-made products on request

1) and the following