

Art. No.	Description	Thickness	Applications	Sample
<b>4750-0</b> <sup>(1)</sup> <b>PUR Ester</b> 42 kg/m <sup>3</sup> Grey (55)	<ul style="list-style-type: none"> <li>Open-cell sealing tape with PET-film intermediate carrier for over expansion protection</li> <li>Mod. solvent acrylic adhesive</li> <li>Perm. temperature resistance 120°C</li> </ul>	<b>4751-0:</b> 3 mm <b>4752-0:</b> 4 mm <b>4753-0:</b> 6 mm <b>4754-0:</b> 5 mm <b>4755-0:</b> 9 mm <b>4756-0:</b> 12 mm	<ul style="list-style-type: none"> <li>Sealing tape in luminaries</li> <li>Sealing tape for soft storage and sealing of goods</li> <li>Soft storage of electrical, acoustics, and measuring devices</li> <li>Acoustic and sound insulation</li> </ul>	
<b>4760-0</b> <sup>(1)</sup> <b>PUR Ester</b> 42 kg/m <sup>3</sup> Black (04) White (08)	<ul style="list-style-type: none"> <li>Open-cell sealing tape with PET-film intermediate carrier for over expansion protection</li> <li>Mod. water based acrylic adhesive</li> </ul>	<b>4761-0:</b> 3 mm <b>4763-0:</b> 6 mm <b>4765-0:</b> 9 mm <b>4766-0:</b> 12 mm	<ul style="list-style-type: none"> <li>Sealing tape against drafts, dust etc.</li> <li>Sealing of formwork joints for exposed (fair-faced) concrete</li> <li>Soft storage of sensitive components</li> <li>Protection against vibration on machines and devices</li> </ul>	
<b>1890-0</b> <sup>(1)</sup> <b>PUR Ester</b> 28 kg/m <sup>3</sup> Black (04) White (08)	<ul style="list-style-type: none"> <li>Open-celled sealing tape with PET-film intermediate carrier for over expansion protection</li> <li>Mod. water based acrylic adhesive</li> </ul>	<b>1891-0:</b> 3 mm <b>1892-0:</b> 4 mm <b>1893-0:</b> 6 mm <b>1894-0:</b> 8 mm <b>1895-0:</b> 9 mm <b>1896-0:</b> 10 mm <b>1897-0:</b> 12 mm	<ul style="list-style-type: none"> <li>Sealing tape against drafts, dust etc.</li> <li>Sealing in lighting and window construction industries</li> <li>Acoustic and sound insulation</li> <li>Shock-absorbing, sealing tape</li> <li>Protection against vibration on machines and devices</li> </ul>	
<b>60490-1</b> <sup>(1)</sup> <b>EPDM</b> 130 kg/m <sup>3</sup> Black (04)	<ul style="list-style-type: none"> <li>Closed-cell sealing tape with fleece carrier for over expansion protection</li> <li>Mod. water based acrylic adhesive</li> <li>Weather, age, and UV resistant</li> <li>Resistant to a variety of organic and inorganic solvents</li> </ul>	<b>60490-1:</b> 2 mm <b>60491-1:</b> 3 mm <b>60492-1:</b> 4 mm <b>60493-1:</b> 6 mm <b>60494-1:</b> 8 mm <b>60495-1:</b> 5 mm <b>60496-1:</b> 10 mm <b>60497-1:</b> 15 mm <b>60498-1:</b> 9 mm <b>60499-1:</b> 1 mm	<ul style="list-style-type: none"> <li>Sealing tape against drafts, dust, moisture etc.</li> <li>Sealing of electrical cabinets and electrical machines</li> <li>Protection against vibration on machines and devices</li> <li>Acoustic and sound insulation of speakers</li> <li>Gaskets, underlays and die-cuts for the automotive industry</li> </ul>	
<b>1720</b> <sup>(1)</sup> <b>APTK</b> 170 kg/m <sup>3</sup> Black (04)	<ul style="list-style-type: none"> <li>Closed-cell sealing tape without any intermediate carrier</li> <li>Mod. water based acrylic adhesive</li> <li>Weather, age, and UV resistant</li> <li>Resistant to a variety of organic and inorganic solvents</li> </ul>	<b>1720:</b> 2 mm <b>1721:</b> 3 mm <b>1722:</b> 4 mm <b>1723:</b> 6 mm <b>1724:</b> 8 mm <b>1725:</b> 5 mm <b>1726:</b> 10 mm <b>1727:</b> 12 mm	<ul style="list-style-type: none"> <li>Sealing tape against drafts, dust, moisture, etc.</li> <li>Sealing of electrical cabinets and electrical machines</li> <li>Protection against vibration on machines and devices</li> <li>Acoustic and sound insulation of speakers</li> <li>Gaskets, underlays and die-cuts for the automotive industry</li> </ul>	
<b>1710</b> <sup>(1)</sup> <b>PE</b> 30 kg/m <sup>3</sup> Black (04) White (08)	<ul style="list-style-type: none"> <li>Closed-cell sealing tape without any intermediate carrier</li> <li>Hotmelt adhesive</li> <li>Weather, age, and UV resistant</li> <li>Resistant to a variety of organic and inorganic solvents, alkalis, and acids</li> </ul>	<b>1710:</b> 2 mm <b>1711:</b> 3 mm <b>1712:</b> 4 mm <b>1713:</b> 5 mm <b>1714:</b> 6 mm <b>1715:</b> 8 mm <b>1716:</b> 10 mm	<ul style="list-style-type: none"> <li>Window tape</li> <li>Sealing of air-conditioning ducts, dome lights, solar power systems, ventilation, mechanical and apparatus construction</li> <li>Secure sealing of structural parts on walls, ceilings and floors</li> <li>Sealing of formwork joints for exposed (fair-faced) concrete</li> <li>Impact sound and vibration insulation</li> </ul>	
<b>2710</b> <sup>(1)</sup> <b>PE</b> 30 kg/m <sup>3</sup> Black (04) White (08)	<ul style="list-style-type: none"> <li>Closed-cell sealing tape with a laminated film on the back of the foam</li> <li>Hotmelt adhesive</li> <li>Weather, age, and UV resistant</li> <li>Resistant to a variety of organic and inorganic solvents, alkalis, and acids</li> </ul>	<b>2710:</b> 2 mm <b>2711:</b> 3 mm <b>2712:</b> 4 mm <b>2713:</b> 5 mm <b>2714:</b> 6 mm <b>2715:</b> 8 mm <b>2716:</b> 10 mm	<ul style="list-style-type: none"> <li>Window tape</li> <li>Secure sealing of structural parts on walls, ceilings and floors</li> <li>Prefabrication of partition wall panels</li> <li>Impact sound insulation in partition wall construction</li> <li>Sealing in ventilation, mechanical and apparatus engineering</li> </ul>	
<b>1700</b> <sup>(1)</sup> <b>PVC</b> 160 kg/m <sup>3</sup> Light grey (18)	<ul style="list-style-type: none"> <li>Closed-cell sealing tape without any intermediate carrier</li> <li>Mod. water based acrylic adhesive</li> <li>Weather, age, and UV resistant</li> <li>Very flexible and conformable</li> </ul>	<b>1700:</b> 2 mm <b>1701:</b> 3 mm <b>1702:</b> 4 mm <b>1703:</b> 5 mm <b>1704:</b> 6 mm	<ul style="list-style-type: none"> <li>Sealing in air-conditioning and exhaust systems</li> <li>Stacking intermediate layer for the glass industry</li> <li>Transport protection of metal, plastic, and wood panels</li> </ul>	
<b>4700-1</b> <sup>(1)</sup> <b>PVC</b> 200 kg/m <sup>3</sup> White (08)	<ul style="list-style-type: none"> <li>Closed-cell sealing tape with fleece carrier for over expansion protection</li> <li>Mod. water based acrylic adhesive</li> <li>Weather, age, and UV resistant</li> <li>Resistant to a variety of organic and inorganic solvents, alkalis, acids, etc.</li> </ul>	<b>4700-1:</b> 2 mm <b>4702-1:</b> 4 mm	<ul style="list-style-type: none"> <li>Sealing tape against dust and moisture in electrical devices, such as refrigerators, washing machines, dishwashers, etc.</li> <li>Noise and rattle protection in vehicle, housing and ship construction</li> <li>Stacking intermediate layer in the glass industry</li> <li>Transport protection of metal, plastic, and wood, plates</li> </ul>	
<b>1741/-93</b> <b>EPDM</b> 280 kg/m <sup>3</sup> White (08)	<ul style="list-style-type: none"> <li>Closed-cell sealing profile, scrim reinforced for over expansion protection</li> <li>Hotmelt Adhesive</li> <li>Age and UV resistant, chemically neutral</li> </ul>	<b>1741:</b> K-profile <b>1793:</b> P-profile <b>1741:</b> 3,5 mm <b>1793:</b> 5,5 mm	<ul style="list-style-type: none"> <li>Sealing tape against acid, alkalis, solvents, and other aggressive chemicals</li> <li>Sealing tape in green house and window industries</li> <li>Sealing tape in aerospace, automotive, etc.</li> </ul>	
<b>25810</b> <sup>(1)</sup> <b>Keratape</b> 300 kg/m <sup>3</sup> White (08)	<ul style="list-style-type: none"> <li>Single sided, self-adhesive, asbestos-free, high-temperature, fibre-glass tape with fleece intermediate carrier</li> <li>Mod. water based acrylic adhesive</li> <li>Max. operating temperature 1100°</li> </ul>	<b>25810:</b> 2 mm <b>25811:</b> 3 mm <b>25812:</b> 4 mm <b>25813:</b> 5 mm <b>25814:</b> 6 mm	<ul style="list-style-type: none"> <li>Used in high temperature applications</li> <li>Sealing tape for special fire code protections and other security requirements</li> <li>Non-cancerous</li> </ul>	
<b>51130/31</b> <b>PUR</b> 150 kg/m <sup>3</sup> Black (04)	<ul style="list-style-type: none"> <li>Impregnated PUR flexible foam</li> <li>Acrylic adhesive with flame retardant additives</li> <li>Compliant with DIN 18542 BG1 (51130) / BG2 (51131)</li> <li>Vapour permeability</li> </ul>	on request	<ul style="list-style-type: none"> <li>Sealing of acoustic noise, driving rain, dust, drafts, splash water, and loss of heat</li> <li>Sealing tape in facade construction, drywall and metal construction</li> <li>51130 = Sealing up to 600 PA (Wind speed Bft. 11)</li> <li>51131 = Sealing up to 300 PA (Wind speed Bft. 9)</li> </ul>	

Custom-made products on request

1) and the following