

Art. No.	Description	Thickness	Applications	Sample
4750-0 ⁽¹⁾ PUR Ester 42 kg/m ³ Grey (55)	<ul style="list-style-type: none"> Open-cell sealing tape with PET-Film-intercarrier as overexpansion protection Mod. water based Acrylic Adhesive Perm. Temperature Resistance 120°C 	4751-0: 3 mm 4752-0: 4 mm 4753-0: 6 mm 4754-0: 5 mm 4755-0: 9 mm 4756-0: 12 mm	<ul style="list-style-type: none"> Sealing tape in luminaries Sealing tape for soft storage and sealing of goods Soft storage of electrical, acoustics and measuring devices Acoustic and sound insulation 	
4760-0 ⁽¹⁾ PUR Ester 42 kg/m ³ Black (04) White (08)	<ul style="list-style-type: none"> Open-celled sealing tape with PET-Film-intercarrier as overexpansion protection Mod. water based Acrylic Adhesive 	4761-0: 3 mm 4763-0: 6 mm 4765-0: 9 mm 4766-0: 12 mm	<ul style="list-style-type: none"> Sealing tape against supply air, dust etc. Sealing of formwork joints for exposed concrete Soft storage of sensitive components Protection against vibration on machines and devices 	
1890-0 ⁽¹⁾ PUR Ester 28 kg/m ³ Black (04) White (08)	<ul style="list-style-type: none"> Open-celled sealing tape with PET-Film-intercarrier as overexpansion protection Mod. water based Acrylic Adhesive 	1891-0: 3 mm 1892-0: 4 mm 1893-0: 6 mm 1894-0: 8 mm 1895-0: 9 mm 1896-0: 10 mm 1897-0: 12 mm	<ul style="list-style-type: none"> Sealing tape against supply air, dust etc. Sealing in luminaries and window industries Acoustic and sound insulation Shock-absorbing sealing tape Protection against vibration on machines and devices 	
60490-1 ⁽¹⁾ EPDM 130 kg/m ³ Black (04)	<ul style="list-style-type: none"> Closed-cell sealing tape with Fleece carrier as overexpansion protection Mod. water based Acrylic Adhesive Resistant to age and UV, weather-resistant Resistant to a multiplicity of organic and inorganic solvents 	60490-1: 2 mm 60491-1: 3 mm 60492-1: 4 mm 60493-1: 6 mm 60494-1: 8 mm 60495-1: 5 mm 60496-1: 10 mm 60497-1: 15 mm 60499-1: 1 mm	<ul style="list-style-type: none"> Sealing tape against supply air, dust, moisture etc Sealing of electrical cabinets and electrical machines Protection against vibration on machines and devices Acoustic and sound insulation of speakers Gaskets, Underlay and die-cuts for automotive industries 	
1720 ⁽¹⁾ APT K 170 kg/m ³ Black (04)	<ul style="list-style-type: none"> Closed-cell sealing tape without any intercarrier Mod. water based Acrylic Adhesive Resistant to age and UV, weather-resistant Resistant to a multiplicity of organic and inorganic solvents 	1720: 2 mm 1721: 3 mm 1722: 4 mm 1723: 6 mm 1724: 8 mm 1725: 5 mm 1726: 10 mm 1727: 12 mm	<ul style="list-style-type: none"> Sealing tape against supply air, dust, moisture etc Sealing of electrical cabinets and electrical machines Protection against vibration on machines and devices Acoustic and sound insulation of speakers Gaskets, Underlay and die-cuts for automotive industries 	
1710 ⁽¹⁾ PE 30 kg/m ³ Black(04) White (08)	<ul style="list-style-type: none"> Closed-cell sealing tape without any intercarrier Hotmelt Adhesive Resistant to age and UV, weather-resistant Resistant to a multiplicity of organic and inorganic solvents, leaching and acid 	1710: 2 mm 1711: 3 mm 1712: 4 mm 1713: 5 mm 1714: 6 mm 1715: 8 mm 1716: 10 mm	<ul style="list-style-type: none"> Windows tape Sealing of air conditions, roof light dome, solar systems, ventilation, machine and apparatus construction Safe sealing between structural parts on wall, ceiling and floor Sealing of formwork joints for exposed concrete Impact sound insulation 	
2710 ⁽¹⁾ PE 30 kg/m ³ Black(04) White (08)	<ul style="list-style-type: none"> Closed-cell sealing tape with a laminated Film on the back of the foam Hotmelt Adhesive Resistant to age and UV, weather-resistant Resistant to a multiplicity of organic and inorganic solvents, leaching and acid 	2710: 2 mm 2711: 3 mm 2712: 4 mm 2713: 5 mm 2714: 6 mm 2715: 8 mm 2716: 10 mm	<ul style="list-style-type: none"> Windows tape Sealing of air conditions, roof light dome, solar systems, ventilation, machine and apparatus construction Safe sealing between structural parts on wall, ceiling and floor Sealing of formwork joints for exposed concrete Impact sound insulation 	
1700 ⁽¹⁾ PVC 160 kg/m ³ Light grey (18)	<ul style="list-style-type: none"> Closed-cell sealing tape without any intercarrier Mod. water based Acrylic Adhesive Resistant to age and UV, weather-resistant Very soft and cuddly 	1700: 2 mm 1701: 3 mm 1702: 4 mm 1703: 5 mm 1704: 6 mm	<ul style="list-style-type: none"> Sealing in air conditions and evacuation systems Stacking intermediate layer in glass industries Transport protection of plates made of metal, plastic and wood etc. 	
4700-1 ⁽¹⁾ PVC 200 kg/m ³ White (08)	<ul style="list-style-type: none"> Closed-cell sealing tape with Fleece carrier as overexpansion protection Mod. water based Acrylic Adhesive Resistant to age and UV, weather-resistant Resistant to a multiplicity of organic and inorganic solvents, leaching and acid 	4700-1: 2 mm 4702-1: 4 mm	<ul style="list-style-type: none"> Sealing tape against supply air, dust, moisture etc. in electrical devices, such as fridges, washing machines, dishwashers etc., acoustic and sound insulation Stacking intermediate layer in glass industries Transport protection of plates made of metal, plastic and wood etc. 	
1741/-93 EPDM 280 kg/m ³ White (08)	<ul style="list-style-type: none"> Closed-cell sealing profile with grid scrim as overexpansion protection Hotmelt Adhesive Resistant to age and UV, chemically neutral 	1741: K-profile 1793: P-profile 1741: 3,5 mm 1793: 5,5 mm	<ul style="list-style-type: none"> Sealing tape against acid, leaching and solvents and other aggressive chemicals Sealing tape in green house an window industries Sealing tape in aerospace and automotive etc. 	
25810 ⁽¹⁾ Keratape 300 kg/m ³ White (08)	<ul style="list-style-type: none"> Single sided self adhesive, asbestos-free High-Temperature-Fibre-Glass tape with Fleece intercarrier Mod. water based Acrylic Adhesive max. operating temperature 1100° 	25810: 2 mm 25811: 3 mm 25812: 4 mm 25813: 5 mm 25814: 6 mm	<ul style="list-style-type: none"> used in High Temperature Applications Sealing tape for additional requirements of special fire protections or security requirements Not cancer-causing 	
51130/31 PUR 150 kg/m ³ Black(04)	<ul style="list-style-type: none"> Impregnated PUR flexible foam Acrylic with flame retardant additives fulfilled DIN 18542 BG1 (51130) / BG2 (51131) vapour permeability 	on request	<ul style="list-style-type: none"> Sealing of acoustic noise, driving rain, dust, supply air, splash water and loss of heat, sealing tape for structural-facing sectors, dry and metal construction 51130 = Sealing up to 600 PA (Storm force 11) 51131 = Sealing up to 300 PA (Storm force 9) 	

Custom-made products on request

1) and the following